

TRABUILT FASTENER SELECTION GUIDE

	Standard Fastener	Heavy Duty Fastener	XHD® Fastener	#12 ASAP [®] with Steel Plate	#12 ASAP [®] with Plastic Plate	Masonry Anchor
THREAD DIA./STYLE	#12 / modified buttress	#14 / AB symmetrical thread	#15 / modified buttress, mini drill point	#12 / modified buttress	#12 / modified buttress	Zinc alloy with zinc-plated steel pin
DECKTYPES	18 – 24 ga. steel, wood	18 – 22 ga. steel, wood, concrete (¾16" pilot hole)	18 – 24 ga. steel, wood	18 – 24 ga. steel, wood	18 – 24 ga. steel, wood	Concrete
FOR USE WITH	3" Insulation Plate	3" Insulation Plate, 2" Seam Plate	3" Insulation Plate, 2" Seam Plate	Comes with Steel Insulation Plate	Comes with Plastic Insulation Plate	Lip Bar orTerm Bar
LENGTHS	15/8", 21/4", 3" – 8"	1¼", 1¾", 2" – 24" Call for lengths over 12"	1¾", 2" – 16"	15/8", 21/4", 3" – 8"	21/4", 3" – 8"	1", 1¼", 1½", 2"
	Insulation Plate	Insulation Plate	Seam Plate	Barbed Seam Plate	Lip Bar	Flat Bar
	Insulation Plate	Insulation Plate	Seam Plate	Barbed Seam Plate	Lip Bar	Flat Bar
SIZE			Seam Plate 2" round Galvalume steel	2" round Galvalume steel	3/4" wide with 1/4" x 3/6" holes Aluminum	

XHD® and ASAP® are registered trademarks of OMG, Inc. Copyright © 2016 OMG, Inc. All rights reserved.



100 PACKS Heavy Duty Fastener

Masonry Anchor

Hercules Retro Drain






THREAD DIA./STYLE	#14 / AB symmetrical thread	Zinc alloy with zinc-plated steel pin	
DECKTYPES	18 – 22 ga. steel, wood, concrete (¾16" pilot hole)	Concrete	
FOR USE WITH	3" Insulation Plate, 2" Seam Plate	Lip Bar orTerm Bar	
LENGTHS	1¾", 2", 3", 4", 5", 6"	7/8", 1", 1¼", 1½", 2"	




- •Easy to install from rooftop
- •Large drain flange
- •10" dia. strainer dome
- •12" drain stem
- •Mechanical compression seal
- •3", 4", 5" and 6" sizes

100 PACKS Insulation Plate

Seam Plate





4	SIZE	3" round	2" round	
	MATERIAL	Galvalume steel	Galvalume steel	
	SPACING	NA	NA	