

ROOF X TENDER® 986 Super Silicone Deep Tint Base

SECTION 1: PRODUCT & COMPANY IDENTIFICATION

PRODUCT NAME:	ROOF X TENDER® 986	DISTRIBUTED BY:	Beacon Sales Acquisition, Inc.
PRODUCT NUMBER:	RX-9865	ADDRESS:	505 Huntmar Park Drive, Suite 300 Herndon, VA 20170
CATEGORY:	White Liquid	PHONE:	571-323-3939
PRODUCT USE:	White Elastomeric Roof Coating	INTERNET:	www.becn.com
MANUFACTURER:	APOC		
ADDRESS:	4161 E. 7th Avenue Tampa, FL 33605		
PHONE:	813-248-2101		
EMERGENCY PHONE:	CHEMTREC: 1-800-424-9300 Outside USA and Canada: +703-527-3887		
EFFECTIVE DATE:	4/19/2018		

Section 2 - Hazards Identification

Emergency Overview

WARNING

Causes mild skin irritation. Harmful if swallowed.

- Prevention** Do not handle until all safety precautions have been read and understood. Use personal protective equipment as required. Wash thoroughly after handling.
- Response** IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If skin irritation occurs: Get medical advice/attention.
- Storage/Disposal** Store in a closed container. Do not allow product to freeze. Dispose of content and/or container in accordance with local, regional, national, and/or international regulations.


ROOF X TENDER® 986 Super Silicone Deep Tint Base



Classification:
 Eye irritation, Category 2A
 Skin sensitization, Category 1
 Carcinogenic, Category 2

Statements of Hazard:
 Warning
 H319 Causes serious eye irritation
 H317 May cause allergic skin reaction
 H351 Suspected of causing cancer

Precautions for Safe Handling:
 P102 Keep out of the reach of children
 P201 Obtain special instructions before use
 P202 Do not handle until all safety precautions have been read and understood
 P261 Avoid breathing vapors or mists
 P264 Wash hands thoroughly after handling
 P272 Contaminated work clothing should not be allowed out of the workplace
 P281 Use personal protective equipment as required



CAUTION - May cause eye and skin irritation on contact.

Physical Form	* Liquid
Color	* White Liquid.
Odor	* Paint-Like Odor.
Flash Point	* 185 F(85 C)
OSHA	* Irritant
WHMIS	* Class D - Poisonous and Infectious Materials - Division 2 - Subdivision B



GHS

- * Skin Corrosion/Irritation - Category 1
- Serious Eye Damage, Eye Irritation - Category 2A
- Carcinogenic – Category 2B

NFPA: **Health : 2** **Flammability: 1** **Reactivity: 0** **Personal Protection: G**

Potential Health Effects

Inhalation

Acute (Immediate) * Inhalation of vapors or mists may cause central nervous system depression, light-headedness, headache, nausea and loss of coordination.

Chronic (Delayed) * Under normal conditions of use, no health effects are expected.

Skin

Acute (Immediate) * May cause irritation.

Chronic (Delayed) * Repeated and prolonged exposure to the skin may cause dermatitis.

Eye

Acute (Immediate) * Likely to cause eye irritation, burning, tearing, etc. on contact with the eyes. If swelling and irritation persist, seek medical attention.

Chronic (Delayed) * Direct contact may cause slight to moderate irritation.

ROOF X TENDER® 986 Super Silicone Deep Tint Base

Ingestion

Acute (Immediate)

* May cause irritation. May affect the nervous system. May be harmful or fatal if swallowed.

Chronic (Delayed)

* Repeated and prolonged exposure may cause gastrointestinal disturbances including diarrhea, nausea, and vomiting.

Carcinogenic Effects			
	CAS	IARC	NTP
Titanium Dioxide	13463-67-7	Group 2B-Possible Carcinogen	Evidence of Carcinogenicity

Section 3 - Composition/Information on Ingredients

Hazardous Components					
Chemical Name	Identifiers	%(weight)	LD50/LC50	Classifications According to Regulation/Directive	Comments
Dimmethyl Polysiloxe	CAS: 70131-67-8	45.0%	LD50 Oral - rat - > 62.080 mg/kg		
Silica Quartz	CAS: 68476-25-5	34.0%			
Polydimethyl Siloxane	CAS: 63148-62-9	10.0%			
Methyltrimethyl Siloxane	CAS: 1185-55-3	3.0%	LD50 Oral, rat = 12,500 mg/kg		
Titanium Dioxide	CAS: 13463-67-7	6.0%	LD50 Oral, rat - 60 gm/kg		
Fumed Silica	CAS: 112945-52-5	1.0%			
Aminopropyl Trimethoxy Silane	CAS: 13822-56-5	1.0%	LD50 Oral - rat - > 62.080 mg/kg		

Non-Hazardous Components					
Chemical Name	Identifiers	%(weight)	LD50/LC50	Classifications According to Regulation/Directive	Comments

This product is an encapsulated mixture which reduces the likelihood of exposure to hazardous particulates. Airborne exposures to hazardous dusts or mists may be generated by spraying, sanding or grinding.

Section 4 - First Aid Measures

Inhalation

* IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If signs/symptoms continue, get medical attention.

Skin

* Rinse skin immediately with plenty of water for 15-20 minutes. Take off contaminated clothing. If skin irritation occurs: Get medical advice/attention.

Eye

* If eye irritation persists: Get medical advice/attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Ingestion

* If swallowed, do not induce vomiting: seek medical advice immediately and show this container or label.

Section 5 - Fire Fighting Measures

ROOF X TENDER® 986 Super Silicone Deep Tint Base

Extinguishing Media	* LARGE FIRE: Water spray, fog or regular foam. SMALL FIRES: Dry chemical, CO2, water spray or regular foam.
Unsuitable Extinguishing Media	* No data available.
Firefighting Procedures	* Fire fighters should wear complete protective clothing including self-contained breathing apparatus. Keep unauthorized personnel away.
Unusual Fire and Explosion Hazards	* Product containers may rupture when exposed to extreme heat. Precautions should be taken to prevent release of materials.
Hazardous Combustion Products	* Non-combustible, substance itself does not burn but may decompose upon heating to produce toxic fumes.
Protection of Firefighters	* Structural firefighters' protective clothing provides limited protection in fire situations ONLY; it is not effective in spill situations where direct contact with the substance is possible.
Flash Point	* 185 F(85 C) CC (Closed Cup)

Section 6 - Accidental Release Measures

Personal Precautions	* Do not touch damaged containers or spilled material unless wearing appropriate protective clothing.
Emergency Procedures	* Isolate the area and contain the spilled material. Persons not wearing the appropriate PPE should be removed from the area until the spill is cleaned up.
Environmental Precautions	* Avoid run off to waterways and sewers.
Containment/Clean-up Measures	* Absorb or cover with dry earth, sand or other non-combustible material and transfer to containers. Use appropriate Personal Protective Equipment (PPE)
Prohibited Materials	* Avoid contact with strong oxidizing agents and acids.

Section 7 - Handling and Storage

Handling	* KEEP OUT OF THE REACH OF CHILDREN! Keep containers tightly closed when not in use.
Storage	* Avoid extreme temperatures and freezing. Keep container/package tightly closed and in a well-ventilated place.
Special Packaging Materials	* Not Applicable.
Incompatible Materials or Ignition Sources	* Avoid contact with strong oxidizing agents and acids.

Section 8 - Exposure Controls/Personal Protection

Personal Protective Equipment

Pictograms



Respiratory

* Use with adequate ventilation. A respirator is required. Use a NIOSH-approved air purifying respirator with organic vapor cartridge or supplied air respirator. This product is an encapsulated mixture which reduces the likelihood of exposure to hazardous particulates. Airborne exposures to hazardous dusts or mists may be generated by spraying, sanding or grinding.

Eye/Face

* Wear ANSI approved safety glasses with side shields or safety goggles.

ROOF X TENDER® 986 Super Silicone Deep Tint Base

Hands

* Wear chemical resistant gloves with repeated or prolonged exposure.

Engineering Measures/Controls

* Adequate ventilation systems as needed to control concentrations of airborne contaminants below applicable threshold limit values. Use precaution to protect building intake from fumes and vapors created outdoors.

Exposure Limits/Guidelines					
	Result	Canada Ontario	Mexico	NIOSH	OSHA
Titanium Dioxide (13463-67-7)	TWAs	10 mg/m3 TWAEV (total dust)	10 mg/m3 TWA (as Ti)	10 mg/m3 - TWA	15 mg/m3 TWA (total dust)
Fumed Silica (112945-52-5)	TWAs	10 mg/m3-TWAEV		6 mg/m3-TWA	6 mg/m3-TWA

Section 9 - Physical and Chemical Properties

Material Description			
Physical Form	Liquid	Appearance/Description	White liquid with heavy consistency.
Color	White Liquid.	Odor	Paint-Like Odor.
Taste	No data available.	Particulate Type	Not relevant
Particulate Size	Not relevant	Aerosol Type	Not relevant
Odor Threshold	No data available		
General Properties			
Boiling Point	>300 F	Melting Point	No data available
Decomposition Temperature	No data available	Heat of Decomposition	Not relevant
pH	8 @ 25 C(77 F)	Specific Gravity/Relative Density	1.33 Water=1
Density	11.10 lbs/gal @ 25 C(77 F)	Bulk Density	No data available
Water Solubility	Soluble 0 % @ 25 C(77 F)	Solvent Solubility	Not relevant
Viscosity	4,000 cps. @ 25 C(77 F)		
Volatility			
Vapor Pressure	5.3 mmHg (torr) @ 20 C(68 F)	Vapor Density	> 1 Air=1
Evaporation Rate	< 0.7 Ether = 1	VOC (Wt.)	No data available
VOC (Vol.)	<10 g/L	Volatiles (Wt.)	No data available
Volatiles (Vol.)	No data available		
Flammability			
Flash Point	185 F (85 C)	Flash Point Test Type	CC (Closed Cup)
UEL	No data available	LEL	No data available
Autoignition	No data available	Self-Accelerating Decomposition Temperature (SADT)	Not relevant
Heat of Combustion (ΔHc)	Not relevant	Burning Time	Not relevant
Flame Duration	Not relevant	Flame Height	Not relevant
Flame Extension	Not relevant	Ignition Distance	Not relevant
Environmental			
Half-Life	Not relevant	Octanol/Water Partition coefficient	Not relevant
Coefficient of Water	Not relevant	Bioaccumulation Factor	Not relevant
Bioconcentration Factor	Not relevant	Biochemical Oxygen Demand BOD/BOD5	Not relevant
Chemical Oxygen Demand	Not relevant	Persistence	Not relevant
Degradation	Not relevant		

Section 10 - Stability and Reactivity

ROOF X TENDER® 986 Super Silicone Deep Tint Base

Stability	* Stable under normal temperatures and pressures.
Hazardous Polymerization	* Hazardous polymerization not indicated.
Conditions to Avoid	* Excessive heat and freezing.
Incompatible Materials	* Strong oxidizers and acids.
Hazardous Decomposition Products	* No known issues under normal usage conditions.

Section 11 - Toxicological Information

Component Name	CAS	Data
Dimmethyl Polysiloxe	70131-67-8	Acute Toxicity: LD50 Oral - rat - > 62.080 mg/kg
Methyltrimethyl Siloxane	1185-55-3	Acute Toxicity: LD50 Oral, rat = 12,500 mg/kg
Titanium Dioxide	13463-67-7	Acute Toxicity: LD50 Oral, rat · 60 gm/kg
Aminopropyl Trimethoxy Silane	13822-56-5	Acute Toxicity: LD50 Oral - rat - > 62.080 mg/kg

Other Component Information	* IARC has concluded that the following chemicals in this product are carcinogenic to humans(Group 1): ACGIH has designated the following chemicals in this product as suspected human carcinogens (A2): silica, quartz. NTP has listed the following chemicals in this product as known human carcinogens:. Risk of cancer depends on duration and level of exposure to this product as a dust or aerosol mist.
------------------------------------	--

Section 12 - Ecological Information

Ecological Fate	* No data available.
Persistence/Degradability	* No data available.
Bioaccumulation Potential	* No data available.
Mobility in Soil	* No data available.
Other Information	* Do not allow product exposure to the ground or into any waterway. Do not allow entry into municipal sewer systems.

Section 13 - Disposal Considerations

Product	* Dispose of content and/or container in accordance with local, regional, national, and/or international regulations.
----------------	---

Section 14 - Transportation Information

DOT - United States - Department of Transportation - Shipping Name: Not Regulated.

TDG - Canada - Transportation of Dangerous Goods - Shipping Name: Not Restricted.

IMO/IMDG - International Maritime Transport Shipping Name: Not Regulated.

International Air Transportation Association – Not Regulated

ROOF X TENDER® 986 Super Silicone Deep Tint Base

Section 15 - Regulatory Information

SARA Hazard Classifications * Acute, Chronic

State Right To Know					
Component	CAS	MA	MN	NJ	PA
Dimmethyl Polysiloxane	70131-67-8	No	No	Yes	Yes
Silica Quartz	68476-25-5	No	No	Yes	Yes
Polydimethyl Siloxane	63148-62-9	Yes	Yes	No	Yes
Methyltrimethyl Siloxane	1185-55-3	No	No	No	No
Titanium Dioxide	13463-67-7	Yes	Yes	Yes	Yes
Fumed Silica	112945-52-5	Yes	Yes	Yes	Yes
Aminopropyl Trimethoxy Silane	13822-56-5	No	No	Yes	Yes

Inventory			
Component	CAS	EU EINECS	TSCA
Dimmethyl Polysiloxane	70131-67-8	No	No
Silica Quartz	68476-25-5	No	No
Polydimethyl Siloxane	63148-62-9	No	No
Methyltrimethyl Siloxane	1185-55-3	No	Yes
Titanium Dioxide	13463-67-7	No	Yes
Fumed Silica	112945-52-5	No	No
Aminopropyl Trimethoxy Silane	13822-56-5	No	No

Canada

Labor

Canada - WHMIS - Classifications of Substances

Dimmethyl Polysiloxane	70131-67-8	45%	D2B
Silica Quartz	68476-25-5	34%	D2B
Methyltrimethyl Siloxane	1185-55-3	3%	D2B
Titanium Dioxide	13463-67-7	6%	D2A

United States

Environment

U.S. - CERCLA/SARA - Hazardous Substances and their Reportable Quantities

Silica Quartz	68476-25-5	34%
Polydimethyl Siloxane	63148-62-9	10%
Methyltrimethyl Siloxane	1185-55-3	3%

United States - California

Environment

U.S. - California - Proposition 65 - Carcinogens List

Polydimethyl Siloxane	63148-62-9	10%
-----------------------	------------	-----

United States - Rhode Island

Labor

U.S. - Rhode Island - Hazardous Substance List

ROOF X TENDER® 986 Super Silicone Deep Tint Base

Titanium Dioxide	13463-67-7	6%
Fumed Silica	112945-52-5	1%
Aminopropyl Trimethoxy Silane	13822-56-5	1%

Other Information * WARNING: This product contains a chemical known to the State of California to cause cancer.

Section 16 - Other Information

Preparation Date * 6/8/2016

Last Revision Date * 6/8/2016

Disclaimer/Statement of Liability

This information relates to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is to the best of our knowledge and belief, accurate and reliable as of the date compiled. However, no representation, warranty or guarantee is made as to its accuracy, reliability or completeness. It is the user's responsibility to verify the suitability and completeness of such information for particular use. Gardner Gibson or Beacon Sales Acquisition does not accept liability for any loss or damage that may occur from the use of this information.