



TRIBUILT® 200 POLYURETHANE SEALANT

PRODUCT DESCRIPTION

TRIBUILT® 200 Polyurethane sealant is comprised of polyurethane technology with adhesion to many common substrates, offering high performance and durability. Meets ASTM C920. Uses can include: metal, steel, glass, painted surfaces, vinyl, brick, concrete and other common building substrates.

FEATURES AND BENEFITS

ADHESION TO VARIOUS SUBSTRATES

Adhesion to most common residential and light commercial building substrates.

WEATHER RESISTANCE

Durability-no deterioration observed after 250hrs of UV exposure

TACK-FREE TIME

3-9 hours

NO ODOR AND NON-STAINING

SOLVENT FREE

APPLICATIONS

Demonstrated primerless adhesion to the following substrates:

- Aluminum
- Steel
- Glass
- Painted Surfaces
- Vinyl



PACKAGING

10.2 FL oz Cartridges

TEMPERATURE RANGE

40-120 degrees Fahrenheit

COLOR

White

TEST	PROPERTY	UNIT	RESULT
ASTM C639	Rheological Properties		Non Sagging
ASTM C679	Tack Free Time	Hours	3-9
ASTM C661	Durometer Hardness, Shore A	Points	45
ASTM D1708	Secant Modulus At 100%	PSI	75-90
ASTM D1708	Tensile Strength	PSI	280-380
ASTM D1708	% Elongation	%	900-1100
ASTM C719	Joint Movement Capabilities, Extension / Compression	%	+25
ASTM C794	Peel Strength	lbf/in	15-35*