

TRI-BUILT® BUILDING WRAP SYSTEMS

TRI-BUILT® offers industry-leading building envelope products for the residential and commercial markets. TRI-BUILT® Building Wraps feature a wide variety of performance criteria designed to suit specific climates and applications. When compared to competitive products TRI-BUILT® Building Wraps offer unmatched performance and value.

Custom Printing is available in full vivid colors, with alternating messages, and at the largest size in the industry — all at a low cost. In short, there may be other custom printing out there, but there’s nothing like TRI-BUILT® Building Wrap custom printing

BUILDING WRAP FEATURES	TRI-BUILT H	TRI-BUILT C	TRI-BUILT PLUS	TRI-BUILT H/C
Weight (LBS/MSF)	18.4	16.4	14.7	13.3
Tensile Strength (lbs/in, MD)	71	65	30	53
Tensile Strength (lbs/in, CD)	50	45	30	46
Tear Strength (lbf/MD)	63	8	64	63
Tear Strength (lbf, CD)	64	10	63	64
Water Ponding	Pass	Pass	Pass	Pass
Water Resistance (minutes)	>60	>120	>60	>60
MVTR (perms)	12	60	56	10
Hydrostatic Waterhead (cm H ₂ O)	500	350	186	Pass
Flame Spread	Class A	Class A	Class A	Class A
Air Resistance	Pass	Pass	Pass	Pass
UV Exposure (max days)	180	180	120	300

FLASHING TAPE FEATURES	TRI-BUILT STRAIGHT	TRI-BUILT FLEX
Thickness (mils)	11	57
Minimum Application Temperature (F)	20 F	20 F
Service Temperature Range	-20/180 F	-20/180 F
Primer Needed	NO	NO
Sealability around Nails	PASS	PASS
Adhesive	Modified Butyl	Modified Butyl
UV Exposure (days)	180	180