



TRI-BUILT® ASPHALT SATURATED ORGANIC FELT NO. 30 ASTM D226

PRODUCT DESCRIPTION

TRI-BUILT® Asphalt Saturated Organic Felt NO. 30 ASTM D226 features a tough organic felt (non-perforated) that is saturated with asphalt. It is accepted for use as an underlayment felt to be applied over the deck prior to the installation of asphalt shingles or other suitable roof covering.

CERTIFICATIONS

U.L. Prepared Roofing Accessory
ASTM D 226, Type II

PRODUCT DATA

NO. 30 ASTM D226

Roll Dimensions	72' X 36"
Square feet per roll	2 Squares
Laying Lines	2", 4", 17"

All values stated as nominal

CAUTION: This product contains wood dust. Wood dust has been classified as a "known" human carcinogen by the International Agency for Research on Cancer (IARC) and the National Toxicology Program. This product also contains oxidized asphalt. Occupational exposures to oxidized asphalt and its emissions during roofing have been classified by IARC as a "probable human carcinogen". Oxidized asphalt also contains Polycyclic Aromatic Hydrocarbons some of which have been classified by IARC as known or probable human carcinogens. The physical nature of this product may help limit any inhalation or dermal hazard during application and/or removal. However, physical forces such as sawing, grinding or drilling during demolition work and heating or burning may increase the inhalation or dermal exposure hazard of this product. Take precautions to prevent breathing and contact with skin.



FBC Approved