

Low-Slope Residential Solutions



S

TRI-BUIILT® offers low-slope membranes in colors that match our most popular shingles for a variety of application options. Now you can coordinate a low-slope roof to an adjacent shingle roof with any low-slope application method with these TRI-BUILT membranes:

TRI-BUILT® SA Cap (Self-Adhered)



• 12 Year Warranty

TRI-BUILT® SBS Cap (Hot Asphalt or Cold Adhesive)



• 12 Year Warranty

TRI-BUILT® Smooth Torch



TRI-BUILT® Granulated Torch



• 10 Year Warranty

	_OW-	S	lope	R	Resic	len	tia	ISo	lut	ior	1S
--	------	---	------	---	-------	-----	-----	-----	-----	-----	----

Colors	SA Cap	Torch	SBS Cap
White	.	s	S
Moiré Black	s	S	S
Heather Blend	S	s	
Weathered Woo	d S	S	S
Burnt Sienna	s,	S.	\$
Resawn Shake	S	s	S

TRI-BUILT® TRI-BUILT® TRI-BUILT®

S = Stocked

Colonial Slate

PRODUCT	MATERIAL	REINFORCEMENT	COVERAGE	WEIGHT	THICKNESS	ASTM	ROLLS/PALLET
TRI-BUILT SA CAP	SBS		100 sq. ft.	95 lbs	4.0 mm (160 mils)	D6164, Grade G, Type 1, D7505, D1970	20
TRI-BUILT Granulated Torch	APP	Polyester		103 lbs	4.0 mm (160 mils)	D6222 Grade G, Type 1	
TRI-BUILT Smooth Torch	APP			86 lbs	3.8 mm (140 mils)	D6222, Grade S, Type I	20
TRI-BUILT SBS CAP	SBS			93 lbs	3.7 mm (145 mils)	D6164, Grade G, Type 1	