## TRABUILT





## **COMMON FEATURES**

- Reduces energy bills
- Easy installation
- Forever Guarantee residential use only
- Permanently lubricated upper and lower ball bearings that ensure long life and no maintenance
- All-aluminum rust-free construction
- Rigid spider-type structure
- Riveted at every connection
- 21 air-foil curved vanes with rolled edges to deflect water
- Exclusive vari-pitch base adjusts to 12/12 roof pitch
- Large flashing for easy installation
- Tested to withstand winds of 110 m.p.h.
- Reduces winter ice build up
- Big Whirly 14" moves up to 37% more air than the 12"

## COLORS AVAILABLE - B SERIES











12" Whirlybird®

Weathered Bronze



FBC FL3595-R9 14" Whirlybird®

MIAMI-DADE COUNTY 20-0218 02

FBC FL3595-R9

## **BEARING FACTS**

Molded and fully machined raceways - not merely molded. Concentric to .0015 for low drag and quiet operation.

DuPont Delrin® inner and outer bearing rings - the longest lasting and smoothest polymer ball bearing material available.



seals lubricant in and dirt and moisture out.

100 Grade 302 series stainless steel balls for low turning resistance and high resistance to moisture.

TURBINE VENT	Attic floor space to be ventilated in square feet:											
EXHAUST SYSTEMS	1000		1500		2000		2500		3000		3500	
12"	2		2		3		4		4		5	
14"	1		2		2		3		3		4	
Intake												
Selected Turbine Size	12"	14"	12"	14"	12"	14"	12"	14"	12"	14"	12"	14"
C416	21	14	21	28	32	28	42	42	42	42	52	56
C616	15	10	15	19	22	19	29	29	29	29	36	38
C816	8	6	8	11	12	11	16	16	16	16	20	22
105/190	8	5	8	10	11	10	15	15	15	15	18	20
140	6	4	6	8	9	8	12	12	12	12	15	16
SV-10	9	6	9	11	13	11	17	17	17	17	21	22
DA-4/IV-9	15	10	15	20	22	20	29	29	29	29	36	39

Model	Hole Size (in.)	Height (in.)	Base (in.)
B I B-12	12	171⁄4	20 x 20
BEB-12	12	175⁄8	20 x 20
B I B-14	14	20	22 x 22
BEB-14	14	20%	22 x 22